
Travail de Fin d'Etudes : Photonic and thermal properties of periodic arrays of nanometer-wide metal lines

Auteur : Elias, Quentin

Promoteur(s) : Vanderheyden, Benoit

Faculté : Faculté des Sciences appliquées

Diplôme : Master en ingénieur civil physicien, à finalité approfondie

Année académique : 2019-2020

URI/URL : <http://hdl.handle.net/2268.2/10788>

Avertissement à l'attention des usagers :

Tous les documents placés en accès ouvert sur le site le site MatheO sont protégés par le droit d'auteur. Conformément aux principes énoncés par la "Budapest Open Access Initiative"(BOAI, 2002), l'utilisateur du site peut lire, télécharger, copier, transmettre, imprimer, chercher ou faire un lien vers le texte intégral de ces documents, les disséquer pour les indexer, s'en servir de données pour un logiciel, ou s'en servir à toute autre fin légale (ou prévue par la réglementation relative au droit d'auteur). Toute utilisation du document à des fins commerciales est strictement interdite.

Par ailleurs, l'utilisateur s'engage à respecter les droits moraux de l'auteur, principalement le droit à l'intégrité de l'oeuvre et le droit de paternité et ce dans toute utilisation que l'utilisateur entreprend. Ainsi, à titre d'exemple, lorsqu'il reproduira un document par extrait ou dans son intégralité, l'utilisateur citera de manière complète les sources telles que mentionnées ci-dessus. Toute utilisation non explicitement autorisée ci-avant (telle que par exemple, la modification du document ou son résumé) nécessite l'autorisation préalable et expresse des auteurs ou de leurs ayants droit.

UNIVERSITY OF LIÈGE - FACULTY OF APPLIED SCIENCES

GRADUATION STUDIES CONDUCTED FOR OBTAINING THE MASTER'S
DEGREE IN ENGINEERING PHYSICS, 2019-2020

Photonic properties of periodic arrays of nanometer-wide metal lines

Author:

Quentin ELIAS

Supervisors:

Benoît VANDERHEYDEN

Janusz BOGDANOWICZ

Andrzej GAWLIK



August 21, 2020

Abstract

In this master thesis, the interaction of light with periodic arrays of nanometer-wide metal lines was studied. To do so, extensive use of wave optics, waveguide and diffraction grating theories was made to better understand the interaction of light with a structure made of perfect electrical conductor (PEC) lines, both for TE and TM polarizations. In particular, we proposed to gather the results of those theories in an original band structure to understand how light can couple into the array as a function of the geometrical parameters. The structure was viewed as periodic metallic waveguides simultaneously constituting a diffraction grating. The model was used to analyze quantitative numerical finite element calculations of reflectance and transmittance spectra (obtained using COMSOL Multiphysics) and was able to explain the different variations of the spectra, although it could not predict their amplitudes for a given set of geometrical parameters, nor could it predict the proportion of power that was located in each propagating mode of the band structure.

For the PEC array, the pitch was responsible for the activation of waveguide and diffraction modes. Cutoff was observed for TE while extraordinary optical transmission was observed for TM. The width was responsible for the activation of waveguide modes but had no effect on the diffraction modes and had an effect opposite to the pitch. The height was responsible for thin-film interferences which had a strong dependence on the pitch in the case of TE. The TE band structure was able to describe the observations, while the TM one had to be adapted with an effective medium approximation to include a geometric dependence of the TEM mode.

For the copper array, the band structures were slightly different. Due to the absorbing nature of the real metal, there was no sharp cutoff and the effective refractive index varied more smoothly with the pitch. The pitch was also responsible for the activation of both waveguide and diffraction mode, although no cutoff was seen for TE. For the same reasons, the effect of the width on the cutoff was no longer visible for TE, and surface plasmon polaritons (SPPs) could be observed for TM. The thin-film interferences induced by the height were also present but less intense than for PEC, due to the more slowly varying refractive index. The copper TE modes were similar to those of PEC, while the TM modes featured a slight difference in the electric field distribution.

In conclusion, the insight developed by studying an array of PEC lines was crucial to understand the interaction of light with an array of real metal lines. While the TE behavior could be predicted by the corresponding band structure, some particular attention was required by the TM description, which in some cases failed to describe the spectra.