

## **Expert decision support for early design stage of facades for office buildings in Belgium: A parametric approach**

**Auteur :** Nassimos, Meray

**Promoteur(s) :** Attia, Shady

**Faculté :** Faculté des Sciences appliquées

**Diplôme :** Master en ingénieur civil architecte, à finalité spécialisée en ingénierie architecturale et urbaine

**Année académique :** 2020-2021

**URI/URL :** <http://hdl.handle.net/2268.2/13017>

---

### *Avertissement à l'attention des usagers :*

*Tous les documents placés en accès ouvert sur le site le site MatheO sont protégés par le droit d'auteur. Conformément aux principes énoncés par la "Budapest Open Access Initiative"(BOAI, 2002), l'utilisateur du site peut lire, télécharger, copier, transmettre, imprimer, chercher ou faire un lien vers le texte intégral de ces documents, les disséquer pour les indexer, s'en servir de données pour un logiciel, ou s'en servir à toute autre fin légale (ou prévue par la réglementation relative au droit d'auteur). Toute utilisation du document à des fins commerciales est strictement interdite.*

*Par ailleurs, l'utilisateur s'engage à respecter les droits moraux de l'auteur, principalement le droit à l'intégrité de l'oeuvre et le droit de paternité et ce dans toute utilisation que l'utilisateur entreprend. Ainsi, à titre d'exemple, lorsqu'il reproduira un document par extrait ou dans son intégralité, l'utilisateur citera de manière complète les sources telles que mentionnées ci-dessus. Toute utilisation non explicitement autorisée ci-avant (telle que par exemple, la modification du document ou son résumé) nécessite l'autorisation préalable et expresse des auteurs ou de leurs ayants droit.*

---

# Expert decision support for early design stage of facades for office buildings in Belgium: A parametric approach

Design tools, energy approach, Daylighting, Window-to-wall ratio, Grasshopper, simulation

Auteur : Nassimos, Meray

Promoteur : Attia, Shady

Faculté : Faculté des Sciences appliquées

Diplôme : Master en ingénieur civil architecte, à finalité spécialisée en ingénierie architecturale et urbaine

Année académique : 2020-2021

## Summary

---

The facade is one of the most important elements of a building that requires careful planning. In addition to being central in defining a building's identity and image, the facades also contribute to energy consumption and user comfort positively or negatively, especially in an office building, where facades are the main factors that influence energy efficiency.

However, the most important design parameter that integrates into the design process, particularly for window design, is the window-to-wall ratio (WWR). This indicator, with window characteristics, has an impact on the amount of daylight passing inside a room, on the energy use intensity and occupants comfort.

Thus, the main aim of the research presented in this paper is to support the design decision for facades. The methodology was to create a parametric design process for designing façades in Belgium, particularly for office buildings, based on the building's thermal environment performance. First, a simulation through EnergyPlus, Open studio, and Radiance was used with the help of Grasshopper in Rhino. Speed is essential. For that reason, a user-friendly interface tool was developed for this purpose. Thus, it will help designers to choose the desired design based upon a need quickly. Furthermore, designers can use this to do comparative studies to support decision-making for different proposed solutions, especially at the early design stage.

In addition, the study aims to take into account the correlation between facades parameters, such as the Window-to-Wall Ratio (WWR),  $U_{\text{window}}$  value, Solar Heat Gain Coefficient (SHGC), window division, window sill height and building orientation; and thus, study their degree of sensitivity and their impact on visual comfort, thermal comfort and energy efficiency. In addition, a focus on the most influential parameters that we should be aware of during the decision-making is discussed.

Results from different scenarios have been compared, and a sensitivity analysis followed to find the most influential facade parameters. It is demonstrated that WWR has a remarkable influence on daylight metrics and the Solar Heat Gain Coefficient on

energy demand and thermal comfort, with a most negligible impact caused by window sill height and window division. Finally, a focus on the best design cases is mentioned.

In conclusion, this study helps to determine the degree of impact of facade parameters which will lead architects to better understand the influence of each parameter on the results and modify the variables according to their needs using a user-friendly interface.